

In the Specification:

Page 7, after line 19, insert the following:

*A<sub>1</sub>* Figure 7 is an exploded view of a portion of the enlarged cross-section of the probe tip shown in Fig. 6.

line 20, change "7" to --8--;

line 23, change "8" to --9--;

line 24, change "7" to --8--; and

after line 25, insert the following:

--Figure 10 is an end view of the probe tip of the catheter

*A<sub>2</sub>* in the direction 10-10 of Fig. 9.

Page 8, line 1, change "Figure 9" to --Figures 11, 11a, 11b and 11c--, and change "is a schematic diagram" to --are schematic diagrams--.

*NE* Page 19, line 24, change "60-68" to--160-168--.

*NE* Page 20, line 1, change "60" to--160--;

*NE* Line 4, change "62" to--162--;

*NE* Line 5, change "64" to--164--;

*NE* Line 8, change "68" to--168--; and

*NE* Line 10, change "60-68" to--160-168--.

*NE* Page 21, line 21, change "58" to--158--.

*NE* Page 22, line 2, change "62" to--262--;

*NE* Line 3, change "62" to--262--;

*NE* Line 4, change "60" to--260--;

*NE* Line 5, change "64" to--264--;

*NE* Line 11, change "64" to--264--; and

*NE* Line 17 change "its inner surface 62" to--the inner surface of bore 262--.

21